

CUT RESISTANT SLEEVE FOR FULL ARM PROTECTION

Comfortable 22 inch cut resistant sleeve with a secure, adjustable fastening.

FEATURES

- › Full arm cut protection from wrist to shoulder
- › Cut resistant: Level D (EN 388:2016)
- › Lightweight - 13 gauge construction
- › Thinner material on palm and back of hand improves comfort and dexterity when combined with a glove
- › Adjustable VELCRO® Brand hook and loop fastening strap for a secure fit
- › Thumbhole prevents sleeve from rising up and exposing the wrist
- › Light thermal protection up to 100°C for a short period
- › Soft and comfortable to wear
- › Ambidextrous
- › Length: 22 inches (55cm)



SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Glass
- Logistics
- Plastics
- Steel

Suitable Applications

- Castings
- Ductwork
- Engine Servicing
- Glass Handling
- HVAC
- Metalworking
- Sheet Metal Handling

CERTIFICATION

CAT II



EN 388:2016



EN 407:2004



See overleaf for explanation

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE, glass fibre, nylon, spandex
	COATING:	N/A
COLOUR	Grey	
LENGTH (mm)	560	
CUFF STYLE	Elasticated with VELCRO® Brand hook and loop fastener	

RECOMMENDATIONS FOR USE

- USE: Cut resistant sleeve. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
22"	SKY1022	10 pairs per bag 120 pairs per case

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016

PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
					Impact Resistance
					Straight Blade Cut Resistance (EN ISO: 13997)
					Puncture Resistance
					Tear Resistance
					Circular Blade Cut Resistance
					Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



HEAT AND FIRE

EN 407

PERFORMANCE LEVELS

0-4	0-4	0-4	0-4	0-4	0-4
					Resistance to Large Splashes of Molten Metal
					Resistance to Small Drops Of Molten Metal
					Radiant Heat Resistance
					Convective Heat Resistance
					Contact Heat Resistance
					Burning Behaviour

EUROPE

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963