



ORANGE SINGLE USE GLOVE WITH GRIP PATTERN, 100% NITRILE, POWDER FREE, 240MM LONG

High performance, powder-free, orange nitrile single use glove with diamond grip pattern technology. Provides outstanding grip performances and chemical protection.

FEATURES

- > High quality nitrile, soft and durable
- > Palm thickness 0.20mm (7.8mil), weight: 8.5g size M
- High resistance to penetration and projections of many chemicals
- Diamond grip pattern technology on both side offering outstanding grip properties in all conditions
- > Powder-free, latex free, non-sterile, AQL 1.5
- Chlorinated inside to offer more comfort and reduce friction when donning
- Antistatic properties due to inherent antistatic properties of nitrile
- Lasts up to 5 times longer than regular single use gloves in industrial applications
- Ambidextrous for easy and quick donning



SUITABLE FOR

Typical Industries


- Aerospace
- Chemical
- Electronics
- Automotive
- Manufacturing
- Oil and Gas

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Light Assembly
- Engineering
- Repair and Finishing

CAT III See overleaf for explanation EN ISO 3741:2016/Type B EN ISO 374-5: 2016 Virus







Beaded

PRODUCT INFORMATION LINER: Nitrile MATERIALS COATING: N/A COLOUR Orange LENGTH (mm) 240

ORDERING DETAILS

CUFF STYLE

SIZE	CODE	PACKAGING		
8/M	SKG00925GF	100 singles per		
9/L	SKG00925GH	box (90 singles on		
10/XL	SKG00925GJ	size XXL)		
11/XXL	SKG00925GL	10 boxes per case		

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF	BREAKTHROUGH
Α	Methanol	J	n-Heptane	GLOVES	TIME
В	Acetone	K	Sodium hydroxide 40%		. 20 . (
C	Acetonitrile	L	Sulphuric acid 96%	A	≥30 min for at least 6 chemicals
D	Dichloromethane	M	65% Nitric acid		o criennicais
E	Carbon Disulfide	N	99% Acetic acid		≥30 min for at least
F	Toluene	0	25% Ammonium hydroxide	В	3 chemicals
G	Diethylamine	P	30% Hydrogen peroxide		
Н	Tetrahydrofurane	S	40% Hydrofluoric acid	_	≥10 min for at least
1	Ethyl acotato	т	270/ F	_	1 chemical



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)



FOOD CONTACT DIRECTIVE EC 10/2011

EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com +971 4 882 9962 +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2022 Globus (Shetland) Ltd | SKY-DATA-TX925-1222_1